

Multimedia Projector

Vivitek DX977-WT

XGA 高亮度投影機



特色

- XGA (1024 x 768) 解析度
- 超高亮度 6,000 流明以及 15,000:1 對比度
- DLP® DarkChip3™ and BrilliantColor™ 德州儀器高畫質影像處理晶片
- 垂直鏡頭位移, 加上梯形修正.
- 多樣的輸入及輸出介面 (HDMI 1.4b, DisplayPort, VGA, S-Video, Composite Video), communication (RJ45, USB, RS232, 12v trigger) and audio (audio-in/out) I/O options for simplified device connectivity
- 支援 3D 訊號 DLP® Link™ 及 藍光 3D HDMI 1.4b 訊號
- 內建 3W 揚聲器
- 內建 8 種不同的影像模式, 提供不同影像內容最佳畫質

規格

顯示技術	Single 0.7" DLP Technology by TI
亮度	6,000 流明
解析度	XGA (1024 x 768)
支援最大解析	WUXGA (1920x1200)@60Hz
對比度	15,000:1
燈泡壽命/類型	2500/3500/4000 Hours (Normal /Eco. Mode/Dynamic Eco Mode) 310W/245W
投射比	1.43 - 2.14
螢幕尺寸 (對角線)	27.6" – 344.6"
投射距離	1.2m - 10m (3.97' to 32.8')
鏡頭	F/#2.42 - 2.97, f=20.9 - 31.05
變焦	1.5x
螢幕比例	4:3 Native
仰角	112% ±10%
梯形修正	Vertical ±30°
水平頻率	15, 31 – 91Hz
垂直頻率	24 - 30Hz, 47 - 120Hz
鏡頭位移	Vertical:109.5% - 120%, ±5%
3D 支援	Yes (DLP® Link™, HDMI 1.4b (BluRay))
揚聲器	3W (Mono)
支援訊號	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
影像訊號	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
輸入及輸出	VGA-In (x2), HDMI v1.4 (x2), DisplayPort, S-Video, Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, 3D-Sync-Out, Mini-USB (Service)
投影方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (WxDxH)	332.8 x 255 x 114.6mm (13.1 "x 10" x 4.5")
重量	3.95kg (8.7lbs)
顏色	白
噪聲	36dB/30dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
耗能	370W (Normal Mode), 300W (Eco. Mode), <0.5W (Standby Mode) , <6W (LAN Standby Mode)
標準配件	電源線, VGA 訊號線, 遙控器, 鏡頭蓋, 攜行袋, 隨附文件
選購配件	鏡頭,

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

產品圖

